

Spot Usage Transfer Form

Checklist	Included	Comments	
Spot Vision Screener			
Spot Vision Screener ID	_		
Carrying Case			
Spot AC power cord			
Neck Strap			
Printer			
Printer AC power cord			
Ink cartridges in the printer			
Printer Carrier – green Forrester carrier			
Other			
Spare ink cartridges (unopened)			
Two 8GB USB drives			
Stanley Fatmax Inverter (with instructions			
15' Power extension cord w/ 3 head plug			
LED book light			
Stylus pen			
Spot Instruction manual			
HSB OKS Operation Manual			
Printer instruction manual			
cansferred From or Provider	Transf	erred To or Receiver	
me:	Name: _		
ub Name:	Club Na	Club Name:	

Basic Spot Vision Screener Care

- 1. Spot is a precision instrument. It must not be dropped or subjected to physical shock.
- 2. Spot is NOT waterproof. Any minor water droplets on Spot should be wiped off with a soft dry cloth.
 - If accidentally dropped into liquid or spilled on, WelchAllyn Customer Service should be contacted immediately.
- 3. DO NOT leave Spot in excessive heat or cold such as in a car or in direct sunlight. Extreme temperatures can cause the Spot to malfunction
- 4. Spot contains precision electronic circuitry. Never attempt to disassemble Spot yourself. This will void any warranty.
- 5. Do not use cleaners that contain organic solvents to clean Spot's body or front glass.
- 6. For stubborn dirt, use the provided cleaning cloth with a small amount of water or a non-abrasive cleaner. For any questions about proper cleaning procedures, please contact WelchAllyn Customer Service
- 7. When plugging the AC power connector into Spot, be sure not to force the power connector into the Spot device as this may cause damage not covered under warranty.
- 8. The neck and wrist straps on Spot are intended to prevent dropping or it slipping out of a grasp. It is not to be used to carry or support the weight of Spot.

Basic Printer Care

1. Printer ink cartridges always need to be installed in the printer at all times. Never deliver printer without cartridges installed.